

HWB - 15

15 Gallon Hot Water Dispenser



Safety is priority #1 when it comes to staff and customers so we've insulated the top and sides. Our series dispensers are warm, but not too hot to touch, so operation is safe. Guarded faucet protects against cross-contamination.

- At-a-Glance Power and Ready Light
- Fully Insulated Top and Sides
- Drain Valve
- Durable, Stainless Steel Construction
- Controlled Refill

Water Specifications

Water Inlet <i>inch</i>	Flow Rate <i>gpm</i>	Water Pressure <i>psig</i>
3/8 Male Flare	1.5	20-75

Measurements

Height <i>inch</i>	Width <i>inch</i>	Depth <i>inch</i>	Empty Weight <i>lbs</i>	Shipping Weight <i>lbs</i>
28 3/4	20 1/8	27 3/4	86	96

Standard Electrical Configurations

Config. Code	Heater Config.	Voltage	Phase	Wires	KW	Max Amp Draw	Gallons / Per Hour	
							Cold	Hot Water
H15011	2x3.0 KW	120/208	1	3+G	4.6	22.1	11.2	25.8
		120/220			5.3	24.2	12.9	29.9
		120/240			6.1	25.5	14.9	34.3
H15021(1)	3x3.0 KW	120/208	3	4+G	6.9	19.2	16.7	38.6
		120/220			7.9	21.0	19.4	44.8
		120/240			9.1	22.2	22.3	51.5
*H15041(1)	3x3.0 KW	240/415	3	4+G	9.1	12.7	22.3	51.5

*EXPORT ONLY

Specifications subject to change without notice.

(1) Requires 3 Phase Upcharge (Z056)

