

CBS-2021eG
EXTRACTOR® Brewer Series



CBS-2021eG with
 LUXUS® L3D-05
 half gallon dispenser



Cascading Spray Dome

Pulse-Brew Intermittent Spray Shower technology with programmable brew volume • brew time • bypass • pre-wet percent • pre-wet delay • drip delay

FETCO's Cascading Spray Dome (CSD) is the latest breakthrough in extraction technology. The CSD's compact design provides the same full and even saturation as the large sprayhead of the EXTRACTOR® line plus it is easy to remove, clean and replace.

- New Cascading Spray Dome for even & full extraction.
- Compact, stylish design.
- Brews directly into 1/2 gallon LUXUS® Thermal Dispenser.

FETCO® equipment does not contain mercury, lead or fiberglass. Instead we use solid state relays, stainless steel fittings and insulation that do not contain harmful materials.



Water Specifications

Water Inlet <i>inch</i>	Flow Rate <i>gpm</i>	Water Pressure <i>psig</i>
3/8 Male Flare	.25	20-75

Measurements

Height <i>inch</i>	Width <i>inch</i>	Depth <i>inch</i>	Empty Weight <i>lbs</i>	Shipping Weight <i>lbs</i>
27.5	8 3/4	17.0	20	27.1

Standard Electrical Configurations

Config. Code	Heater Config.	Voltage	Phase	Wires	KW	Max Amp Draw	Batches/Hour	
							<i>cold water</i>	<i>hot water</i>
US and Canada								
E20016G	1x2.1 KW	100/130	1	2+G	3.2	14.9/19.2	8.0	8.0
EXPORT								
E20026G	1x3.2 KW	208/240	1	2+G	3.2	11.7/14.0	8.0	8.0

Specifications subject to change without notice.

