



CBS-2031e Single 1.0 Gallon EXTRACTOR® Coffee Brewer

Versatile and reliable .5 -1.0 gallon brewers are the perfect solution for small to medium-sized operations. Conveniently use lightweight, portable Airpots or our LUXUS® Thermal Dispensers to keep coffee hot for hours. Comes standard with the Cascading Spray Dome™.

Brewer Dimensions/Empty Weight
W11 D18 1/4 H26 --35bs

Shipment Dimensions/Weight
W16 D20 H26 --42lbs

Electrical Configuration Code	Heater Configuration	Voltage	Phase	Wires	Kilowatt	Max Amp Draw	Batches/HR Batches/HR (2)	
							Cold Water	Hot Water
E31045(1)	1x1.5 KW	120	1	2+G	1.6	13.0	4.9	11.0
	2x1.5 KW	120/208		3+G	2.4	11.3	7.3	11.0
		120/220			2.6	12.0	8.2	11.0
		120/240			3.1	13.0	9.7	11.0
E31035(1)	1X1.7 KW	120	1	2+G	1.8	14.7	5.5	11.0
	2X1.7KW	120/208		3+G	2.7	12.8	8.3	11.0
		120/220			3.0	13.5	9.2	11.0
		120/240			3.5	14.7	11.0	11.0
E31015(1)	1X2.3 KW	120	1	2+G	2.4	19.7	7.4	11.0
	2X2.3 KW	120/208		3+G	3.6	17.1	11.0	11.0
		120/220			4.1	18.1	11.0	11.0
		120/240			4.7	19.7	11.0	11.0
*E31025 *Export only	1X3.0 KW	220/240	1	2+G	2.6/3.1	12/13	9.7	11.0

Water Inlet (Inch)
3/8 Male Flare

Water Pressure
20-75 psig

Flow Rate
0.25 gpm

For use with the following dispensers:



D051 L3S-10



D041 3.0 SS LINED AIRPOT



D037 1.9 SS LINED SERVER

(1) Can be connected to 120 VAC (Factory Setting) or 120/208-240 VAC

(2) Based on standard factory settings: 4.0 minute brew time: 0% prewet: 200°F water