



CBS-2032e Twin 1/2 to 1.0 Gallon EXTRACTOR® Coffee Brewer

Still as versatile and reliable as the 2031 with .5 -1.0 gallon brewers that are the perfect solution for small to medium-sized operations, but with twice the brewing power. Use the lightweight, portable airpots or our LUXUS® Thermal Dispensers to keep coffee hot for hours. Comes standard with the Cascading Spray Dome™.

Brewer Dimensions/Empty Weight

W19 D18-1/4 H26 -53lbs

Shipment Dimensions/Weight

W24 D23 H26 -64lbs

Electrical Configuration Code	Heater Configuration	Voltage	Phase	Wires	Kilowatt	Max Amp Draw	Batches/HR Cold Water	Batches/HR ⁽¹⁾ Hot Water
E32015	2x3.0 KW	120/208	1	3+G	4.6	22.4	14.6	22.0
		120/220			5.1	23.7	16.9	22.0
		120/240			6.1	25.8	19.4	22.0
*E32025 <i>*Export only</i>	2X3.0 KW	220/240	1	2+G	5.1/6.1	23.7/25.8	19.4	22.0
Water Inlet (Inch)		Water Pressure		Flow Rate				
3/8 Male Flare		20-75 psig		0.5 gpm				

(1) Based on standard factory settings: 4.0 minute brew time: 0% prewet: 200° F water