



CBS-2032ee Twin 1/2 to 1.0 Gallon EXTRACTOR® Coffee Brewer

The ECO mode feature decreases the water temperature setpoint by -30° F after 1-hour of non-use. When in the ECO mode, the user simply presses the STOP button to return to normal operation.

Easier to service: (a) Set threshold for the level control in program mode. (b) Easily test ON/OFF button (c) Display the resistance between the level probe and tank common

Manual hot water faucet delivers fresh, steaming hot water when you need it.

Comes with standard round brew basket and Cascading Spray Dome™. Show with square brew basket accessory.

Brewer Dimensions/Empty Weight
W19 D18-1/4 H26--53lbs

Shipment Dimensions/Weight
W24 D23 H26 --64lbs

Electrical Configuration Code	Heater Configuration	Voltage	Phase	Wires	Kilowatt	Max Amp Draw	Batches/HR	
							Cold Water	Hot Water
E32015E	2x3.0 KW	120/208	1	3+G	4.6	22.4	14.6	22.0
		120/220			5.1	23.7	16.9	22.0
		120/240			6.1	25.8	19.4	22.0

Water Inlet (Inch)
3/8 Male Flare

Water Pressure
20-75 psig

Flow Rate
0.5 gpm

(1) Based on standard factory settings: 4.0 minute brew time: 0% prewet: 200°F water