



CBS-2041e Single 1.0 Gallon EXTRACTOR® Coffee Brewer

Brew directly into our self-serve LUXUS® Thermal Dispensers to serve hot, fresh, aromatic coffee for hours. Comes standard with the Cascading Spray Dome™.

Brewer Dimensions/Empty Weight
W11 D18-1/4 H34-1/4 --46lbs

Shipment Dimensions/Weight
W14 D23 H36 --54lbs

For use with the following dispensers:



D048 L3D-10



D051 L3S-10

Electrical Configuration Code	Heater Configuration	Voltage	Phase	Wires	Kilowatt	Max Amp	Draw	Batches/HR ⁽²⁾	
								Cold Water	Hot Water
E41046 ⁽¹⁾	1x1.5 KW	120	1	2+G	1.6	13.0		3.8	9.3
	2x1.5 KW	120/208		3+G	2.4	11.3		5.8	11.0
		120/220			2.6	12.0		6.5	11.0
		120/240			3.1	13.0		7.7	11.0
E41036 ⁽¹⁾	1X1.7 KW	120	1	2+G	1.8	14.7		4.4	9.3
	2X1.7KW	120/208		3+G	2.7	12.8		6.5	11.0
		120/220			3.0	13.5		7.3	11.0
		120/240			3.5	14.7		8.7	11.0
E41016 ⁽¹⁾	1X2.3 KW	120	1	2+G	2.4	19.7		5.8	9.3
	2X2.3 KW	120/208		3+G	3.6	17.1		8.9	11.0
		120/220			4.1	18.1		9.9	11.0
		120/240			4.7	19.7		11.0	11.0
*E41026 *Export only	1X3.0 KW	220/240	1	2+G	2.6/3.1	12/13		7.7	11.0

Water Inlet (Inch)
3/8 Male Flare

Water Pressure
20-75 psig

Flow Rate
1.0 gpm

(1) Can be connected to 120 VAC (Factory Setting) or 120/208-240 VAC

(2) Based on standard factory settings: 4.0 minute brew time: 0% prewet: 200° F water