

HANDLE OPERATED COFFEE BREWER

CBS-5000 Series

CBS-52H-20

Twin 2.0 Gallon Brewer




Shown with 2.0 Gallon LUXUS® Thermal Dispensers (L4D-20)

The CBS-5000 Series was designed for simplicity. The Handle Operated Series brewers save the operator time and effort by delivering quick and consistent results from your pre-programmed coffee recipe. It is the reliable choice for serving high-volumes of single batch coffee all day long.



Handle operation — a quick start!

Simply twist the handle to begin the brew cycle and in minutes your perfectly brewed coffee is ready to serve.



Manual water faucet.

Safely dispense hot water away from steam and brew basket.



Set it and forget it.

Program your recipe once and this brewer delivers consistent and repeatable results.

FETCO®
TRUSTED | RELIABLE | QUALITY

Water Specification

Water Inlet
3/4" male flare fitting

Minimum Flow Rate
1 1/4 gpm [4.71 lpm]

Water Pressure
20-75 psig [138-517 kPa]


Electrical Configuration

Configuration Code	Heater Configuration	Voltage	Phase	Wires	KW	Electrical Connection	Max Amp Draw	Gallon [Liter] /Hour
US & CANADA								
C53016	2 x 3.0 kW	120/208-240	1	3+G	4.6-6.1	Terminal Block	22.0-25.4	14.0-20.0 [53.0-75.7] ⁽¹⁾
C53026	2 x 4.0 kW	120/208-240	1	3+G	6.1-8.1	Terminal Block	29.3-33.8	20.0-26.0 [75.7-98.4] ⁽¹⁾
C53036 ⁽²⁾	3 x 3.0 kW	120/208-240	3	4+G	7.0-9.1	Terminal Block	19.4-22.4	22.0-30.0 [83.3-113.6] ⁽¹⁾
C53046 ⁽²⁾	3 x 4.0 kW	120/208-240	3	4+G	9.2-12.1	Terminal Block	25.6-29.6	33.0-40.0 [113.6-151.4] ⁽¹⁾
C53186 ⁽²⁾	3 x 4.0 kW	440-480	3	3+G	10.3-12.1	Terminal Block	13.6-14.8	34.0-40.0 [128.7-151.4] ⁽¹⁾
INTERNATIONAL								
C53076 ⁽²⁾	3 x 3.0 kW	220-240/380-415	3	4+G	7.8-9.1	Terminal Block	11.8-12.9	26.0-30.0 [98.4-113.6] ⁽¹⁾
C53086 ⁽²⁾	3 x 4.0 kW	220-240/380-415	3	4+G	10.3-12.1	Terminal Block	15.7-17.1	34.0-40.0 [128.7-151.4] ⁽¹⁾
C53096	2 x 3.0 kW	220-240	1	2+G	5.1-6.1	Terminal Block	23.3-24.4	18.0-20.0 [68.1-75.7] ⁽¹⁾
C53106	2 x 4.0 kW	220-240	1	2+G	6.8-8.1	Terminal Block	30.9-33.8	24.0-26.0 [90.8-98.4] ⁽¹⁾

(1) Based on standard factory settings: 4.0 minute brew time; 0% prewet; 200°F water.
(2) Requires 3 phase Electrical Power System (Z056).

Measurements

Height 39 1/2" [100.3 cm]	Width 21" [53.3 cm]	Depth 16" [40.6 cm]	Empty Weight 87 lbs [39.5 kg]	Filled Weight 150 lbs [68.0 kg]	Shipping Weight 100 lbs [45.4 kg]	Shipping Dimensions: 38" x 23" x 24" [96.5 x 58.4 x 61.0 cm]
-------------------------------------	-------------------------------	-------------------------------	---	---	---	--



Compatible Dispensers

2.0 Gallon LUXUS® Thermal Server (L4S-20)
Must be used with S4S Serving Stations.

D453

2.0 Gallon LUXUS® Thermal Dispenser (L4D-20)

D450

Customize Your Brewer

Single Serving Station for L4S-15/20 Server
Twin Serving Station for L4S-15/20 Server
Triple Serving Station for L4S-15/20 Server
Identifier Plates, Acrylic

A150
A151
A152
A069

Cups per Hour*

8oz. **475** 12oz. **317** 16oz. **238** 20oz. **190**

* Approximate based on maximum power setting.

Paper Coffee Filters

15" x 5.5" (500/Case)

F001

Information

🖱️ fetco.com

✉️ info@fetco.com

📞 847.719.3000
1.800.338.2699 USA
📠 847.719.3001

🏠 **Food Equipment Technologies Co.**
600 Rose Road
Lake Zurich, IL 60047
USA